

EP 30563 (3)

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 December 2001 (06.12.2001)


PCT

(10) International Publication Number
WO 01/93246 A2

- (51) International Patent Classification⁷: **G10L** (US). WANG, Ye-Yi; 6120 142nd Ct. NE, Redmond, WA 98052 (US). MOU, Xiaolong; 60 Wadsworth Street, Apt. 4D, Cambridge, MA 02142 (US).
- (21) International Application Number: PCT/US01/16851
- (22) International Filing Date: 23 May 2001 (23.05.2001) (74) Agents: KOEHLER, Steven, M. et al.; Westman, Champlin & Kelly, P.A., International Centre, Suite 1600, 900 Second Avenue South, Minneapolis, MN 55402-3319 (US).
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 09/585,298 1 June 2000 (01.06.2000) US (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (71) Applicant: MICROSOFT CORPORATION [US/US]; One Microsoft Way, Redmond, WA 98052-6399 (US).
- (72) Inventors: HUANG, Xuedong, D.; 20020 N.E. 121st Street, Woodinville, WA 98072 (US). MAHAJAN, Milind, V.; 17430 N.E. 97th Way, Redmond, WA 98052 (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European

[Continued on next page]

(54) Title: CREATING A LANGUAGE MODEL FOR A LANGUAGE PROCESSING SYSTEM



(57) Abstract: A method (20) for creating a language model from a task-independent corpus is provided. In one embodiment, a task dependent unified language model (140) is created. The unified language model (140) includes a plurality of context-free grammars (144) having non-terminals and a hybrid N-gram model (142) having at least some of the same non-terminals embedded therein.

WO 01/93246 A2



patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *without international search report and to be republished upon receipt of that report*

-1-

CREATING A LANGUAGE MODEL FOR A LANGUAGE PROCESSING
SYSTEM

BACKGROUND OF THE INVENTION

The present invention relates to language
5 modeling. More particularly, the present invention
relates to creating a language model for a language
processing system.

Accurate speech recognition requires more than
just an acoustic model to select the correct word
10 spoken by the user. In other words, if a speech
recognizer must choose or determine which word has
been spoken, if all words have the same likelihood of
being spoken, the speech recognizer will typically
perform unsatisfactorily. A language model provides
15 a method or means of specifying which sequences of
words in the vocabulary are possible, or in general
provides information about the likelihood of various
word sequences.

Speech recognition is often considered to be a
20 form of top-down language processing. Two common
forms of language processing includes "top-down" and
"bottom-up". Top-down language processing begins
with the largest unit of language to be recognized,
such as a sentence, and processes it by classifying
25 it into smaller units, such as phrases, which in
turn, are classified into yet smaller units, such as
words. In contrast, bottom-up language processing
begins with words and builds therefrom, larger

-2-

phrases and/or sentences. Both forms of language processing can benefit from a language model.

One common technique of classifying is to use a formal grammar. The formal grammar defines the sequence of words that the application will allow. One particular type of grammar is known as a "context-free grammar" (CFG), which allows a language to be specified based on language structure or semantically. The CFG is not only powerful enough to describe most of the structure in spoken language, but also restrictive enough to have efficient parsers. Nevertheless, while the CFG provides us with a deeper structure, it is still inappropriate for robust spoken language processing since the grammar is almost always incomplete. A CFG-based system is only good when you know what sentences to speak, which diminishes the value and usability of the system. The advantage of a CFG's structured analysis is thus nullified by the poor coverage in most real applications. For application developers, a CFG is also often highly labor-intensive to create.

A second form of a language model is an N-gram model. Because the N-gram can be trained with a large amount of data, the n-word dependency can often accommodate both syntactic and semantic shallow structure seamlessly. However, a prerequisite of this approach is that we must have a sufficient amount of training data. The problem for N-gram models is that a lot of data is needed and the model may not be

-3-

specific enough for the desired application. Since a word-based N-gram model is limited to n-word dependency, it cannot include longer-distance constraints in the language whereas CFG can.

5 A unified language model (comprising a combination of an N-gram and a CFG) has also been advanced. The unified language model has the potential of overcoming the weaknesses of both the word N-gram & CFG language models. However, there is
10 no clear way to leverage domain-independent training corpus or domain-independent language models, including the unified language models, for domain specific applications.

There thus is a continuing need to develop new
15 methods for creating language models. As technology advances and speech and handwriting recognition is provided in more applications, the application developer must be provided with an efficient method in which an appropriate language model can be created
20 for the selected application.

SUMMARY OF THE INVENTION

A method for creating a language model from a task-independent corpus is provided. In a first aspect, a task dependent unified language model for a
25 selected application is created from a task-independent corpus. The task dependent unified language model includes embedded context-free grammar non-terminal tokens in a N-gram model. The method includes obtaining a plurality of context-free grammars

-4-

comprising non-terminal tokens representing semantic or syntactic concepts of the application. Each of the context-free grammars include words or terminals present in the task-independent corpus to form the semantic or syntactic concepts. The task-independent corpus with the plurality of context-free grammars is parsed to identify word occurrences of each of the semantic or syntactic concepts and phrases. Each of the identified word occurrences are replaced with corresponding non-terminal tokens. A N-gram model is built having the non-terminal tokens. A second plurality of context-free grammars is obtained for at least some of the same non-terminals representing the same semantic or syntactic concepts. However, each of the context-free grammars of the second plurality is more appropriate for use in the selected application.

A second aspect is a method for creating a task dependent unified language model for a selected application from a task-independent corpus. The task dependent unified language model includes embedded context-free grammar non-terminal tokens in a N-gram model. The method includes obtaining a plurality of context-free grammars that has a set of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts and at least one context-free grammar having a non-terminal token for a phrase that can be mistaken for one of the desired task dependent semantic or syntactic concepts. The task-independent corpus with the plurality of

-5-

context-free grammars is parsed to identify word occurrences for each of the semantic or syntactic concepts and phrases. Each of the identified word occurrences is replaced with corresponding non-terminal tokens. A N-gram model is then built having the non-terminal tokens.

A third aspect is a method for creating a language model for a selected application from a task-independent corpus. The method includes obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application. Word phrases are generated from the plurality of context-free grammars. The context-free grammars are used for formulating an information retrieval query from at least one of the word phrases. The task-independent corpus is queried based on the query formulated and text in the task-independent corpus is identified based on the query. A language model is built using the identified text.

A fourth aspect is a method for creating a language model for a selected application from a task-independent corpus. The method includes obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application. Word phrases are generated from the plurality of context-free grammars. First and second N-gram language models are built from the word phrases and the task-independent corpus, respectively. The first N-gram language model and the

-6-

second N-gram language model are combined to form a third N-gram language model.

A fifth aspect is a method for creating a unified language model for a selected application from a corpus. The method includes obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application. A word language model is built from the corpus. Probabilities of terminals of at least some of the context-free grammars are normalized and assigned as a function of corresponding probabilities obtained for the same terminals from the word language model.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a block diagram of a language processing system.

FIG. 2 is a block diagram of an exemplary computing environment.

FIG. 3 is a block diagram of an exemplary speech recognition system.

FIG. 4 is a pictorial representation of a unified language model.

FIGS. 5-8 are flow charts for different aspects of the present invention.

FIG. 9 is a block diagram of another aspect of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATIVE EMBODIMENTS

FIG. 1 generally illustrates a language processing system 10 that receives a language input

-7-

12 and processes the language input 12 to provide a language output 14. For example, the language processing system 10 can be embodied as a speech recognition system or module that receives as the
5 language input 12 spoken or recorded language by a user. The language processing system 10 processes the spoken language and provides as an output, recognized words typically in the form of a textual output.

During processing, the speech recognition system
10 or module 10 can access a language model 16 in order to determine which words have been spoken. The language model 16 encodes a particular language, such as English. In the embodiment illustrated, the language model 16 can be an N-gram language model or
15 a unified language model comprising a context-free grammar specifying semantic or syntactic concepts with non-terminals and a hybrid N-gram model having non-terminals embedded therein. One broad aspect of the present invention is a method of creating or
20 building the language model 16 from a task-independent corpus, several of which are readily available, rather than from a task-dependent corpus, which is often difficult to obtain.

As appreciated by those skilled in the art, the
25 language model 16 can be used in other language processing systems besides the speech recognition system discussed above. For instance, language models of the type described above can be used in handwriting recognition, Optical Character

-8-

Recognition (OCR), spell-checkers, language translation, input of Chinese or Japanese characters using standard PC keyboard, or input of English words using a telephone keypad. Although described below
5 with particular reference to a speech recognition system, it is to be understood that the present invention is useful in building artificial and natural language models in these and other forms of language processing systems.

10 Prior to a detailed discussion of the present invention, an overview of an operating environment may be helpful. FIG. 2 and the related discussion provide a brief, general description of a suitable computing environment in which the invention can be
15 implemented. Although not required, the invention will be described, at least in part, in the general context of computer-executable instructions, such as program modules, being executed by a personal computer. Generally, program modules include routine
20 programs, objects, components, data structures, etc. that perform particular tasks or implement particular abstract data types. Tasks performed by the programs and modules are described below and with the aid of block diagrams and flow charts. Those skilled in the
25 art can implement the descriptions, block diagrams and flow charts as processor executable instructions, which can be written on any form of a computer readable medium. In addition, those skilled in the art will appreciate that the invention can be

-9-

practiced with other computer system configurations, including hand-held devices, multiprocessor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe
5 computers, and the like. The invention can also be practiced in distributed computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules
10 can be located in both local and remote memory storage devices.

With reference to FIG. 2, an exemplary system for implementing the invention includes a general purpose computing device in the form of a
15 conventional personal computer 50, including a processing unit 51, a system memory 52, and a system bus 53 that couples various system components including the system memory to the processing unit 51. The system bus 53 can be any of several types of
20 bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. The system memory includes read only memory (ROM) 54 and a random access memory (RAM) 55. A basic input/output
25 system 56 (BIOS), containing the basic routine that helps to transfer information between elements within the personal computer 50, such as during start-up, is stored in ROM 54. The personal computer 50 further includes a hard disk drive 57 for reading from and

-10-

writing to a hard disk (not shown), a magnetic disk drive 58 for reading from or writing to a removable magnetic disk 59, and an optical disk drive 60 for reading from or writing to a removable optical disk such as a CD ROM or other optical media. The hard disk drive 57, magnetic disk drive 58, and optical disk drive 60 are connected to the system bus 53 by a hard disk drive interface 62, magnetic disk drive interface 63, and an optical drive interface 64, respectively. The drives and the associated computer-readable media provide nonvolatile storage of computer readable instructions, data structures, program modules and other data for the personal computer 50.

Although the exemplary environment described herein employs the hard disk, the removable magnetic disk 59 and the removable optical disk 61, it should be appreciated by those skilled in the art that other types of computer readable media, which can store data that is accessible by a computer, such as magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, random access memories (RAMs), read only memory (ROM), and the like, can also be used in the exemplary operating environment.

A number of program modules can be stored on the hard disk, magnetic disk 59, optical disk 61, ROM 54 or RAM 55, including an operating system 65, one or more application programs 66, other program modules 67, and program data 68. A user can enter commands

-11-

and information into the personal computer 50 through input devices such as a keyboard 70, a handwriting tablet 71, a pointing device 72 and a microphone 92. Other input devices (not shown) can include a joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to the processing unit 51 through a serial port interface 76 that is coupled to the system bus 53, but can be connected by other interfaces, such as a sound card, a parallel port, a game port or a universal serial bus (USB). A monitor 77 or other type of display device is also connected to the system bus 53 via an interface, such as a video adapter 78. In addition to the monitor 77, personal computers typically include other peripheral output devices such as a speaker 83 and a printer (not shown).

The personal computer 50 can operate in a networked environment using logic connections to one or more remote computers, such as a remote computer 79. The remote computer 79 can be another personal computer, a server, a router, a network PC, a peer device or other network node, and typically includes many or all of the elements described above relative to the personal computer 50, although only a memory storage device 80 has been illustrated in FIG. 2. The logic connections depicted in FIG. 2 include a local area network (LAN) 81 and a wide area network (WAN) 82. Such networking environments are

-12-

commonplace in offices, enterprise-wide computer network Intranets and the Internet.

When used in a LAN networking environment, the personal computer 50 is connected to the local area network 81 through a network interface or adapter 83. When used in a WAN networking environment, the personal computer 50 typically includes a modem 84 or other means for establishing communications over the wide area network 82, such as the Internet. The modem 84, which can be internal or external, is connected to the system bus 53 via the serial port interface 76. In a network environment, program modules depicted relative to the personal computer 50, or portions thereof, can be stored in the remote memory storage devices. As appreciated by those skilled in the art, the network connections shown are exemplary and other means of establishing a communications link between the computers can be used.

An exemplary embodiment of a speech recognition system 100 is illustrated in FIG. 3. The speech recognition system 100 includes the microphone 92, an analog-to-digital (A/D) converter 104, a training module 105, feature extraction module 106, a lexicon storage module 110, an acoustic model along with senone trees 112, a tree search engine 114, and the language model 16. It should be noted that the entire system 100, or part of speech recognition system 100, can be implemented in the environment

-13-

illustrated in FIG. 2. For example, microphone 92 can preferably be provided as an input device to the computer 50, through an appropriate interface, and through the A/D converter 104. The training module
5 105 and feature extraction module 106 can be either hardware modules in the computer 50, or software modules stored in any of the information storage devices disclosed in FIG. 2 and accessible by the processing unit 51 or another suitable processor. In
10 addition, the lexicon storage module 110, the acoustic model 112, and the language model 16 are also preferably stored in any of the memory devices shown in FIG. 2. Furthermore, the tree search engine 114 is implemented in processing unit 51 (which can
15 include one or more processors) or can be performed by a dedicated speech recognition processor employed by the personal computer 50.

In the embodiment illustrated, during speech recognition, speech is provided as an input into the
20 system 100 in the form of an audible voice signal by the user to the microphone 92. The microphone 92 converts the audible speech signal into an analog electronic signal, which is provided to the A/D converter 104. The A/D converter 104 converts the
25 analog speech signal into a sequence of digital signals, which is provided to the feature extraction module 106. In one embodiment, the feature extraction module 106 is a conventional array processor that performs spectral analysis on the digital signals and

-14-

computes a magnitude value for each frequency band of a frequency spectrum. The signals are, in one illustrative embodiment, provided to the feature extraction module 106 by the A/D converter 104 at a sample rate of approximately 16 kHz.

The feature extraction module 106 divides the digital signal received from the A/D converter 104 into frames that include a plurality of digital samples. Each frame is approximately 10 milliseconds in duration. The frames are then encoded by the feature extraction module 106 into a feature vector reflecting the spectral characteristics for a plurality of frequency bands. In the case of discrete and semi-continuous Hidden Markov Modeling, the feature extraction module 106 also encodes the feature vectors into one or more code words using vector quantization techniques and a codebook derived from training data. Thus, the feature extraction module 106 provides, at its output the feature vectors (or code words) for each spoken utterance. The feature extraction module 106 provides the feature vectors (or code words) at a rate of one feature vector or (code word) approximately every 10 milliseconds.

Output probability distributions are then computed against Hidden Markov Models using the feature vector (or code words) of the particular frame being analyzed. These probability distributions are later used in

-15-

executing a Viterbi or similar type of processing technique.

Upon receiving the code words from the feature extraction module 106, the tree search engine 114
5 accesses information stored in the acoustic model 112. The model 112 stores acoustic models, such as Hidden Markov Models, which represent speech units to be detected by the speech recognition system 100. In one embodiment, the acoustic model 112 includes a
10 senone tree associated with each Markov state in a Hidden Markov Model. The Hidden Markov models represent, in one illustrative embodiment, phonemes. Based upon the senones in the acoustic model 112, the tree search engine 114 determines the most likely
15 phonemes represented by the feature vectors (or code words) received from the feature extraction module 106, and hence representative of the utterance received from the user of the system.

The tree search engine 114 also accesses the
20 lexicon stored in module 110. The information received by the tree search engine 114 based on its accessing of the acoustic model 112 is used in searching the lexicon storage module 110 to determine a word that most likely represents the codewords or
25 feature vector received from the features extraction module 106. Also, the search engine 114 accesses the language model 16. The language model 16 is a unified language model or a word N-gram or a context-free grammar that is used in identifying the most likely

-16-

word represented by the input speech. The most likely word is provided as output text.

Although described herein where the speech recognition system 100 uses HMM modeling and senone
5 trees, it should be understood that this is but one illustrative embodiment. As appreciated by those skilled in the art, the speech recognition system 100 can take many forms and all that is required is that it uses the language model 16 and provides as an
10 output the text spoken by the user.

As is well known, a statistical N-gram language model produces a probability estimate for a word given the word sequence up to that word (i.e., given the word history H). An N-gram language model
15 considers only (n-1) prior words in the history H as having any influence on the probability of the next word. For example, a bi-gram (or 2-gram) language model considers the previous word as having an influence on the next word. Therefore, in an N-gram
20 language model, the probability of a word occurring is represented as follows:

$$P(w/H) = P(w/w_1, w_2, \dots, w_{(n-1)}) \quad (1)$$

25 where w is a word of interest:

w₁ is the word located n-1 positions prior to the word w;

w₂ is the word located n-2 positions prior to the word w; and

-17-

$w(n-1)$ is the first word prior to word w in the sequence.

Also, the probability of a word sequence is determined based on the multiplication of the probability of each word given its history. Therefore, the probability of a word sequence ($w_1 \dots w_m$) is $P(w_1 \dots w_m) = \prod_{i=1}^m (P(w_i / H_i))$ represented as follows:

(2)

The N-gram model is obtained by applying an N-gram algorithm to a corpus (a collection of phrases, sentences, sentence fragments, paragraphs, etc) of textual training data. An N-gram algorithm may use, for instance, known statistical techniques such as Katz's technique, or the binomial posterior distribution backoff technique. In using these techniques, the algorithm estimates the probability that a word $w(n)$ will follow a sequence of words $w_1, w_2, \dots, w(n-1)$. These probability values collectively form the N-gram language model. Some aspects of the invention described below can be applied to building a standard statistical N-gram model.

As is also well known in the art, a language model can also comprise a context-free grammar. A context-free grammar provides a rule-based model that can capture semantic or syntactic concepts of sentence structure or spoken language. For instance,

-18-

by way of example, one set of context-free grammars of a larger plurality of context-free grammars for a software application or task concerning scheduling meetings or sending electronic mail may comprise:

5

<Schedule Meeting> → <Schedule Command> <Meeting Object>;

<Schedule Command> → book;

<Schedule Command> → schedule;

10 <Schedule Command> → arrange;

etc.

<Meeting Object> → meeting;

<Meeting Object> → dinner;

15 <Meeting Object> → appointment;

<Meeting Object> → a meeting with <Person>;

<Meeting Object> → a lunch with <Person>;

etc.

20 <Person> → Anne Weber;

<Person> → Eric Moe;

<Person> → Paul Toman;

etc.

25 In this example, "< >" denote non-terminals for classifying semantic or syntactic concepts, whereas each of the non-terminals is defined using terminals (e.g. words or phrases) and, in some instances, other non-terminal tokens in a hierarchical structure.

-19-

This type of grammar does not require an in-depth knowledge of formal sentence structure or linguistics, but rather, a knowledge of what words, phrases, sentences or sentence fragments are used in a particular application or task.

A unified language model is also well known in the art. Referring to FIG. 4, a unified language model 140 includes a combination of an N-gram language model 142 and a plurality of context-free grammars 144. Specifically, the N-gram language model 142 includes at least some of the same non-terminals of the plurality of context-free grammars 144 embedded therein such that in addition to predicting words, the N-gram language model 142 also can predict non-terminals. Generally, a probability for a non-terminal can be represented by the following:

$$P(<NT>/h_1, h_2, \dots h_n) \quad (3)$$

where $(h_1, h_2, \dots h_n)$ can be previous words or non-terminals. Essentially, the N-gram language model 142 (also known as a hybrid N-gram model) of the unified language model 140 includes an augmented vocabulary having words and at least some of the non-terminals.

In use, the speech recognition system or module 100 will access the language model 16 (in this embodiment, the unified language model 140) in order to determine which words have been spoken. The N-gram

-20-

language model 142 will be used to first predict words and non-terminals. Then, if a non-terminal has been predicted, the plurality of context-free grammars 144 is used to predict terminals as a function of the non-terminals. However, it should be understood, the particular manner in which the unified language model 140 is used is not critical to the present invention.

As mentioned in the Background section, the application developer should be provided with an efficient method in which an appropriate language model 16 can be created for the selected application. In some applications, a standard N-gram language model will work and any improvements in developing such a model will be valuable. While in other applications, a unified language model 140 may work the best, and accordingly, improvements in building such a model will also be valuable.

As different applications are developed for language processing, task-dependent (domain dependent) language models may be more appropriate, due to their increased specificity, which can also make the language models more accurate than a larger, general purpose language model. However, creating a task-dependent language model is not as easy as creating a general purpose language model. To create a general purpose language model, such as an N-gram language model, a task-independent corpus of training data can be used and applied as discussed above to an

-21-

N-gram algorithm. Task-independent corpora are readily available and can comprise compilations of magazines, newspapers, etc., to name just a few. The task-independent corpora are not directed at any one application, but rather provide many examples of how words are used in a language. Task-dependent corpora, on the other hand, are typically not available. These corpora must be laboriously compiled, and even then, may not be very complete.

10 A broad aspect of the invention includes a method for creating a task or domain dependent unified language model for a selected application from a task-independent corpus. The task-dependent unified language model includes embedded context-free grammar non-terminal tokens in an N-gram language model. As discussed above, the task-independent corpus is a compilation of sentences, phrases, etc. that is not directed at any one particular application, but rather, generally shows, through a wide variety of examples, how words are ordered in a language. Various techniques, described below, have been developed to use the task-independent corpus for creating a language model suitable for a task-dependent application.

25 FIG. 5 illustrates a first method 160 for creating or building a language model. The method 160 includes a step 162 for obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts. As used

-22-

herein, a "semantic or syntactic concept" includes word or word phrases that represent particular word usages for various commands, objects, actions, etc. For instance, the task-independent corpus includes
5 various instances of how proper names are used. For example, the task-independent corpus could have sentences like: "Bill Clinton was present at the meeting" and "John Smith went to lunch at the conference". Although the words used to form the
10 semantic or syntactic concepts in the task-independent corpus may not be those used for the task-dependent application, the task-independent corpus does provide usable examples illustrating the context for the semantic or syntactic concepts. Step
15 162 represents obtaining context-free grammars having non-terminal tokens to represent the semantic or syntactic concepts in the task-independent corpus, the non-terminal tokens having terminals present in the task-independent corpus. For instance, using the
20 proper name example provided above, an example CFG can be the following:

```
<Person> → <Common First Name> [<Common Last  
Name>];  
25 <Common First Name> → John|Bob|Bill|...; (first  
names  
present in the task-independent corpus)
```


-23-

<Common Last Name> → Smith|Roberts|Clinton|...;
(last names present in the task-independent corpus).

5 Commonly, a plurality of context-free grammars comprising non-terminal tokens representing various semantic or syntactic concepts are used. For instance, other semantic or syntactic concepts include geographical places, regions, titles, dates,
10 times, currency amounts, and percentage amounts to name a few. However, it should be understood that these semantic or syntactic concepts are merely illustrative and are not required for practicing the present invention, nor is this list exhaustive of all
15 types of semantic or syntactic concepts, which will depend greatly upon the intended application.

At step 164, the task-independent corpus is parsed with the plurality of context-free grammars obtained in step 162 in order to identify word
20 occurrences in the task-independent corpus of each of the semantic or syntactic concepts.

At step 166, each of the identified word occurrences is replaced with the corresponding non-terminal tokens of step 164. An N-gram model is then
25 built at step 168 using an N-gram algorithm, the N-gram model having the non-terminal tokens embedded therein.

At step 170, a second plurality of context-free grammars is obtained suitable for the selected

-24-

application. In particular, the second plurality of context-free grammars includes at least some of the same non-terminal tokens representing the same semantic or syntactic concepts of step 162. However, 5 each of the context-free grammars of the second plurality is more appropriate for the selected application. Referring back to the proper name example provided above, the second plurality of context-free grammars could include a CFG:

10

```
<Person> → <Titan Incorporated Employee Name>;  
<Titan Incorporated Employee Name> → XD|Ye-  
Yi|Milind|Xiaolong|...; (names of employees in  
Titan Incorporated).
```

15

Method 160 can be implemented in computer 50 wherein each of the context-free grammars and the task-independent corpus are stored on any of the local or remote storage devices. Preferably, the N-gram model having the non-terminal tokens and the 20 second plurality of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts are stored on a computer readable medium accessible by the speech recognizer 25 100.

FIG. 6 illustrates a method 180 for creating a unified language model for a selected application from a task-independent corpus that includes a large number of phrases that may be of different context.

-25-

Simple parsing of the task-independent corpus with context-free grammars for the task-dependent application may cause errors, which will then propagate to the N-gram model upon application of an N-gram algorithm. In order to reduce the errors during parsing, this aspect of the invention includes using at least one context-free grammar having a non-terminal token for a phrase (word or words) that can be mistaken for one of the desired task-dependent semantic or syntactic concepts. In particular, at step 182, a plurality of context-free grammars is obtained. The plurality of context-free grammars includes the set of context-free grammars having non-terminal tokens representing task-dependent semantic or syntactic concepts (i.e. the semantic or syntactic concepts directly pertaining to the selected application) and, at least one context-free grammar having a non-terminal token for a phrase that can be mistaken for one of the desired task-dependent semantic or syntactic concepts. For example, a task-dependent application may require modeling the day of the week as a semantic concept in the N-gram model. A context-free grammar of the following form could be used during parsing of the task-independent corpus:

25

<Day> → Monday|Tuesday|...|Sunday|;

However, the task-independent corpus might contain references to a person called "Joe Friday".

-26-

In order to keep "Friday" as the last name in this instance and, in order to prevent this instance from being parsed as a day, which would then introduce an error into the N-gram model, the plurality of context-free grammars can include a context-free grammar of the form:

5 <Person With Last Name Friday> →
 (Joe|Bill|Bob|...)Friday; (various first names
10 having the last name "Friday").

In this manner, during parsing of the task-independent corpus, instances of days of the week will be identified separate from instances where
15 "Friday" is the last name of an individual.

Step 184 represents parsing the task-independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts. At step 186, each of the
20 identified word occurrences for non-terminals representing concepts which are of interest to the target application is replaced with the corresponding non-terminal token as defined by the corresponding context-free grammar. In other words, the word
25 sequences identified with the extraneous non-terminals which were introduced to prevent parsing errors (such as <Person With Last Name Friday> in the example above) are not replaced with the corresponding non-terminal. An N-gram model can then

-27-

be built having the non-terminal tokens embedded therein as indicated at step 188. Step 190 is similar to Step 170 and includes obtaining a second set of context-free grammars suited for the selected application.

Used during language processing such as speech recognition, the N-gram model having the non-terminal tokens and the plurality of context-free grammars associated with the task-dependent application is stored on a computer readable medium accessible by the speech recognition module 100. However, it is not necessary to include context-free grammars associated with the phrases that can be mistaken for one of the desired task-dependent semantic or syntactic concepts because these context-free grammars are used only to properly parse the task-independent corpus. The phrases associated with these grammars would not normally be spoken in the selected application. Thus, the extent or size of the plurality of context-free grammars is less during speech recognition, corresponding to less required storage space in the computer 50 than was used for parsing the task-independent corpus.

In one embodiment, step 188 associated with building the N-gram model can include eliminating at least some of the associated text from the task-independent corpus for non-terminal tokens that can be mistaken for one of the desired task-dependent semantic or syntactic concepts. In this manner, the

-28-

size of the task-independent corpus is reduced prior to parsing so that method 180 may execute more quickly.

It should also be noted that method 180 can
5 include an additional step of examining the parsed task-independent corpus, or the resulting N-gram model, in order to ascertain errors due to phrases (word or words) that are mistaken for one of the desired task-dependent semantic or syntactic
10 concepts. Appropriate context-free grammars can then be determined and included in the plurality of context-free grammars at step 182. Steps 184 to 188 can then be performed as necessary in order to reexamine the parsed task-independent corpus or N-
15 gram model to ascertain if the errors have been corrected. This iterative process can be repeated as necessary until the errors are corrected and a suitable N-gram model has been obtained.

As discussed above, the task-independent corpus
20 is a general corpus and in fact it is likely that most of the corpus is unrelated to the task or application that the developer is interested in. Nevertheless, the task-independent corpus may contain some text that is relevant to the task or the
25 application. Generally, another aspect of the present invention includes using the context-free grammars for the task-dependent application to form phrases, sentences or sentence fragments that can then be used as queries in an information retrieval

-29-

system. The information retrieval system examines the task-independent corpus and identifies portions similar to the query. The identified text of the task-independent corpus is more relevant to the selected task or application; therefore, a language model derived from the identified text may be more specific than a language model based on the complete task-independent corpus. In addition, although someone who knows about the specific task or application wrote the context-free grammars, he may not know all the various word sequences that can be used for the task or application. This technique narrows the task-independent corpus, but can identify yet more examples of task specific sentences, phrases, etc.

FIG. 7 illustrates a method 200 for creating a language model for a selected application from a task-independent corpus in the manner discussed above. Step 202 includes obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application. As described above, commonly the context-free grammars are written by a developer having at least some knowledge of what phrases may be used in the selected application for each of the semantic or syntactic concepts, but the extent of knowledge about such phrases is not complete. At step 204, word phrases are generated from the plurality of context-free grammars. The word phrases

-30-

can include some or all of the various combinations and permutations defined by the associated context-free grammars where the non-terminal tokens include multiple words.

5 At step 206, at least one query is formulated for an information retrieval system using at least one of the generated word phrases. The query can be generated using a statistical "bag of words" technique which uses TF-IDF vectors. Similarity
10 between the query and segments of the task-independent corpus can be computed using cosine similarity measure. These are generally well-known techniques in the field of information retrieval. Alternatively, the query can include Boolean logic
15 ("and", "or", etc.) as may be desired to combine word phrases. However, each query could be simply a separate word phrase, as appreciated by those skilled in the art.

At step 208, the task-independent corpus is
20 queried based on the query formulated. The particular information retrieval technique used to generate and execute the query against the task-independent corpus is not critical to this feature of the present invention. Rather, any suitable query
25 development and information retrieval technique can be used. It should simply be noted that the language model created from the identified text according to the present technique works better with information

-31-

retrieval techniques that identify more relevant text of the task-independent corpus.

The text identified in the task-independent corpus based on the query is indicated at step 210.
5 A language model can then be built using the identified text as represented at step 212.

At this point, it should be noted that the method illustrated in FIG. 7 is not limited to a unified language model, or even an N-gram language
10 model, but rather, can be helpful in forming language models of any type used in a language processing system where the model is based on a task-independent corpus. Nevertheless, the method 200 is particularly useful in building an N-gram language model. In the
15 case of an N-gram language model or a hybrid N-gram language model, step 212 will commonly require use of an N-gram algorithm.

FIG. 8 illustrates a method 220 similar to the method 200 of FIG. 7 wherein the same reference
20 numerals have been used to identify similar steps. However, method 220 can be used to create an N-gram language model having the non-terminal tokens of the context-free grammars. In addition to the steps described above, method 220 also includes parsing the
25 identified text of the task-independent corpus with a plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts as indicated at step 222. Step 224 then includes replacing each of the identified word

-32-

occurrences with corresponding non-terminal tokens for selected non-terminals (i.e. excluding the non-terminals which may have been introduced to prevent mistakes during parsing). Step 212 would then include building an N-gram model having non-terminal tokens. In both methods 200 and 220, the relevant text is identified in the task-independent corpus. If desired, the identified text can be extracted, copied or otherwise stored separate from the task-independent corpus as an aid in isolating relevant text and providing easier processing.

FIG. 9 is a block diagram illustrating another aspect of the present invention. Generally, this aspect includes forming an N-gram language model from the word phrases obtained from the context-free grammars and combining the N-gram language model with another N-gram language model based on the task-independent corpus. In the embodiment illustrated in FIG. 9, block 240 represents the context-free grammars obtained (for example, authored by the developer) for the selected task or application. The context-free grammars are used to generate synthetic data or word phrases 242 in a manner similar to step 204 of methods 200 and 220. The word phrases 242 are then provided to an N-gram algorithm 244 to build a first N-gram language model 246.

FIG. 9 also illustrates in block diagram form steps 206, 208, and 210 where the context-free grammars are used to formulate an information

-33-

retrieval query from at least one of the phrases, query the task-independent corpus based on the query formulated, identify associated text in the task-independent corpus based on the query, and build a
5 second N-gram language model from the identified text. Block 248 illustrates application of an N-gram algorithm to obtain the second N-gram language model 250.

A third N-gram language model 252 is formed by
10 combining the first N-gram language model 246 and the second N-gram language model 250. This combination can be performed using any known smoothing technique, such as interpolation, deleted interpolation, or any other suitable technique. If desired, the second
15 language model can be weighted based on whether the identified text is believed to be accurate. The weighting can be based on the amount of text identified in the task-independent corpus, the number of queries used, etc.

20 In another embodiment, non-terminal tokens representing semantic or syntactic concepts can be inserted into the identified text, or the task-independent corpus in order that the second N-gram language model includes non-terminal tokens. This
25 option is illustrated in dashed lines for block 264 and arrows 266 and 268. Of course, if this option is chosen the identified text 210 would not be provided directly to the N-gram algorithm 248, but rather to block 264. The non-terminal tokens inserted into the

-34-

identified text or the task-independent corpus can be based on the context-free grammars obtained at block 240, or alternatively, based on another set of context-free grammars 270 that includes other
5 context-free grammars for the reasons discussed above. When the third N-gram language model 252 is built having non-terminals, the word phrases or synthetic data at block 242 typically will also include the non-terminals as well.

10 When the context-free grammars are used to generate synthetic data, probabilities for the word phrases formed with the non-terminals and the terminals of the non-terminals can be chosen as desired; for instance, each can be assigned equal
15 probability.

The task-dependent unified language model includes embedded context-free grammar non-terminal tokens in an N-gram as well as a plurality of context-free grammars defining the non-terminal
20 tokens. Inside each context-free grammar, the standard probabilistic context-free grammar can be used. However, without real data pertaining to the specific task or application, an estimate for each of the terminal probabilities cannot be easily
25 determined. In other words, the developer can author or otherwise obtain the plurality of context-free grammars; however, an estimate of the probabilities for each of the terminals may not be readily known. Although a uniform distribution of probabilities can

-35-

be used, another aspect of the present invention includes assigning probabilities to terminals of at least some of the context-free grammars as a function of corresponding probabilities obtained for the same terminals from the N-gram language model built from the task-independent corpus. Preferably, assigning probabilities to terminals of the context-free grammars includes normalizing the probabilities of the terminals from the N-gram language model in each of the context-free grammars as a function of the terminals in the corresponding context-free grammar. In other words, the context-free grammar constrains or defines the allowable set of terminals from the N-gram language model. Therefore, probabilities of the terminals from the N-gram language model need to be appropriately normalized in the same probability space as the terminals present in the corresponding context-free grammar.

In one embodiment, an input utterance $W = w_1 w_2 \dots w_s$ can be segmented into a sequence $T = t_1 t_2 \dots t_m$ where each t_i is either a word in W or a context-free grammar non-terminal that covers a sequence of words $\overline{u_i}$ in W . The likelihood of W under the segmentation T is therefore

$$P(W, T) = \prod_{i=1}^m P(t_i | t_{i-2}, t_{i-1}) \prod_{i=1}^m P(\overline{u_i} | t_i) \quad (4)$$

In addition to tri-gram probabilities, we need to include $P(\overline{u_i} | t_i)$, the likelihood of generating

-36-

a word sequence $\bar{u}_{t_i} = [u_{t_i,1} u_{t_i,2} \dots u_{t_i,k}]$ from the context-free grammar non-terminal t_i . In the case when t_i itself is a word ($\bar{u}_{t_i} = [t_i]$), $P(\bar{u}_{t_i} | t_i) = 1$. Otherwise, $P(\bar{u}_{t_i} | t_i)$ can be obtained by predicating each word in the sequence on its word history:

$$P(\bar{u}_{t_i} | t_i) = \prod_{l=1}^{|\bar{u}_{t_i}|} P(u_{t_i,l} | u_{t_i,1}, \dots, u_{t_i,l-1}) P(</s> | \bar{u}_{t_i}) \quad (5)$$

Here $</s>$ represents the special end-of-sentence word. Three different methods are used to calculate the likelihood of a word given history inside a context-free grammar non-terminal.

A history $h = u_{t_i,1} u_{t_i,2} \dots u_{t_i,l-1}$ corresponds to a set $Q(h)$, where each element in the set is a CFG state generating the initial $l-1$ words in the history from the non-terminal t_i . A CFG state constrains the possible words that can follow the history. The union of the word sets for all of the CFG states in $Q(h)$, $W_Q(h)$ defines all legal words (including the symbol " $</s>$ " for exiting the non-terminal t_i if

$t_i \Rightarrow u_{t_i,1} u_{t_i,2} \dots u_{t_i,l-1}$) that can follow the history according to the context-free grammar constraints. The likelihood of observing $u_{t_i,l}$ following the history can be estimated by the uniform distribution below:

$$P(u_{t_i,l} | h) = 1 / \|W_Q(h)\|. \quad (6)$$

The uniform model does not capture the empirical word distribution underneath a context-free grammar

-37-

non-terminal. A better alternative is to inherit existing domain-independent word tri-gram probabilities. These probabilities need to be appropriately normalized in the same probability space. Even though we have used word tri-gram models to illustrate the technique, it should be noted that any word-based language model can be used here including word-level N-grams with different N. Also, the technique is applicable irrespective of how the word language models are trained (in particular whether task-independent or task-dependent corpus is used). Thus we have:

$$P(u_{t,l} | h) = \frac{P_{word}(u_{t,l} | u_{t,l-2}, u_{t,l-1})}{\sum_{w \in W_Q(h)} P_{word}(w | u_{t,l-2}, u_{t,l-1})} \quad (7)$$

Another way to improve the modeling of word sequence covered by a specific CFG non-terminal is to use a specific word tri-gram language model $P_t(w_n | w_{n-2}, w_{n-1})$ for each non-terminal t . The normalization is performed the same as in Equation (7).

Multiple segmentations may be available for W due to the ambiguity of natural language. The likelihood of W is therefore the sum over all segmentations $S(W)$:

$$P(w) = \sum_{T \in S(W)} P(W, T) \quad (8)$$

-38-

Although the present invention has been described with reference to preferred embodiments, workers skilled in the art will recognize that changes may be made in form and detail without
5 departing from the spirit and scope of the invention.

What is Claimed:

1. A method for creating a task dependent unified language model for a selected application from a task independent corpus, the task dependent unified language model being for use in a language processing system and having embedded context-free grammar non-terminal tokens in a N-gram model, the method comprising:

obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts, each of the context-free grammars having words present in the task independent corpus to form the semantic or syntactic concepts;

parsing the task independent corpus with the plurality of context-free grammars to identify word occurrences of each of the semantic or syntactic concepts;

replacing each of the identified word occurrences with corresponding non-terminal tokens;

building a N-gram model having the non-terminal tokens; and

obtaining a second plurality of context-free grammars comprising at least some of the same non-terminals representing the same semantic or syntactic concepts, each of the context-free grammars of the second

-40-

plurality being more appropriate for use in the selected application.

2. The method of claim 1 and further comprising:
storing the N-gram model having the non-terminal tokens and the second plurality of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts on a computer readable medium.

3. A method for creating a task dependent unified language model for a selected application from a task independent corpus, the task dependent unified language model being for use in a language processing system and having embedded context-free grammar non-terminal tokens in a N-gram model, the method comprising:

obtaining a plurality of context-free grammars comprising a set of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts and at least one context-free grammar having a non-terminal token for a phrase that can be mistaken for one of the desired task dependent semantic or syntactic concepts;

parsing the task independent corpus with the plurality of context-free grammars to

-41-

identify word occurrences for each of the semantic or syntactic concepts and phrases; replacing each of the identified word occurrences with corresponding non-terminal tokens; and building a N-gram model having the non-terminal tokens.

4. The method of claim 3 wherein replacing each of the identified word occurrences includes excluding the non-terminals added for the prevention of mistakes during parsing.
5. The method of claim 3 and further comprising:
storing the N-gram model having the non-terminal tokens and the set of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts on a computer readable medium.
6. The method of claim 3 wherein building the N-gram model includes eliminating at least some of the associated text from the task independent corpus for non-terminal tokens that can be mistaken for one of the desired task dependent semantic or syntactic concepts.
7. A method for creating a language model for a selected application from a task independent corpus, the language model being for use in a language processing system, the method comprising:

-42-

obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application;
generating word phrases from the plurality of context-free grammars;
formulating an information retrieval query from at least one of the word phrases;
querying the task independent corpus based on the query formulated;
identifying associated text in the task independent corpus based on the query; and
building a language model using the identified text.

8. The method of claim 7 wherein building a language model comprises building a N-gram language model.

9. The method of claim 8 and further comprising:
parsing the identified text of the task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts;
replacing each of the identified word occurrences with corresponding non-terminal tokens; and
wherein building the N-gram language model comprises building a N-gram model having the non-terminal tokens.

-43-

10. The method of claim 8 and further comprising:
building a second N-gram language model from the
word phrases generated from the plurality of
context-free grammars; and
combining the first-mentioned N-gram language
model and the second N-gram language model
to form a third N-gram language model.
11. The method of claim 10 and further comprising:
parsing the identified text of the task
independent corpus with the plurality of
context-free grammars to identify word
occurrences for each of the semantic or
syntactic concepts;
replacing each of the identified word occurrences
with corresponding non-terminal tokens; and
wherein the word phrases include non-terminal
tokens and wherein building the first-
mentioned N-gram language model comprises
building a N-gram model having the non-
terminal tokens.
12. The method of claim 9 and further comprising:
storing the N-gram model having the non-terminal
tokens and the plurality of context-free
grammars having non-terminal tokens
representing task dependent semantic or

-44-

syntactic concepts on a computer readable medium.

13. The method of claim 7 and further comprising:
storing the identified text of the task independent corpus separate from the task independent corpus.

14. A method for creating a language model for a selected application from a task independent corpus, the language model being for use in a language processing system, the method comprising:

obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application;

generating word phrases from the plurality of context-free grammars;

building a first N-gram language model from the word phrases;

formulating an information retrieval query from at least one of the word phrases;

querying the task independent corpus based on the query formulated;

identifying associated text in the task independent corpus based on the query; and

building a second N-gram language model from the identified text; and

-45-

combining the first N-gram language model and the second N-gram language model to form a third N-gram language model.

15. The method of claim 14 wherein building the second N-gram language model includes using only the identified text.

16. The method of claim 15 and further comprising:
storing the identified text of the task independent corpus separate from the task independent corpus.

17. The method of claim 16 and further comprising:
parsing the identified text of the task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts;
replacing each of the identified word occurrences with corresponding non-terminal tokens; and
wherein the word phrases include non-terminal tokens and wherein building the first-mentioned N-gram language model comprises building a N-gram model having the non-terminal tokens.

18. The method of claim 14 and further comprising:

-46-

parsing the task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts; replacing each of the identified word occurrences with corresponding non-terminal tokens; and wherein the word phrases include non-terminal tokens and wherein building the first-mentioned N-gram language model comprises building a N-gram model having the non-terminal tokens.

19. A method for creating a unified language model for a selected application from a corpus, the method comprising:

obtaining a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application;
building a word language model from the corpus;
and
assigning probabilities to words of at least some of the context-free grammars as a function of corresponding probabilities obtained for the same words from the word language model wherein assigning probabilities includes normalizing the probabilities of the words from the language model in each of the context-free grammars as a function of the

-47-

words allowed by the corresponding context-free grammar.

20. The method of claim 19 wherein the word language model comprises an N-gram language model.

21. The method of claim 19 wherein the corpus comprises a task independent corpus.

22. The method of claim 21 and further comprising:
generating word phrases from the plurality of context-free grammars;
formulating an information retrieval query from at least one of the word phrases;
querying the task independent corpus based on the query formulated;
identifying associated text in the task independent corpus based on the query; and
wherein building a N-gram language model includes using the identified text.

23. A computer readable medium including instructions readable by a computer which, when implemented execute a method to build a task dependent unified language model for a language processing system, the method comprising:

accessing a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts, each of the

-48-

context-free grammars having words present in a task independent corpus to form the semantic or syntactic concepts;
parsing the task independent corpus with the plurality of context-free grammars to identify word occurrences of each of the semantic or syntactic concepts;
replacing each of the identified word occurrences with corresponding non-terminal tokens;
building a N-gram model having the non-terminal tokens; and
storing the N-gram model and a second plurality of context-free grammars comprising at least some of the same non-terminals representing the same semantic or syntactic concepts, each of the context-free grammars of the second plurality being more appropriate for use in the selected application.

24. A computer readable medium including instructions readable by a computer which, when implemented execute a method to build a task dependent unified language model for a language processing system, the method comprising:

accessing a plurality of context-free grammars comprising a set of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts and at least one context-free grammar having a

-49-

non-terminal token for a phrase that can be mistaken for one of the desired task dependent semantic or syntactic concepts; parsing a task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts and phrases; replacing each of the identified word occurrences with corresponding non-terminal tokens; and building a N-gram model having the non-terminal tokens.

25. The computer readable medium of claim 24 wherein replacing each of the identified word occurrences with corresponding non-terminal tokens includes excluding the non-terminals added for the prevention of mistakes during parsing.

26. The computer readable medium of claim 24 having instructions further comprising:

storing the N-gram model having the non-terminal tokens and the set of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts on a computer readable medium.

27. The computer readable medium of claim 24 wherein building the N-gram model includes eliminating at least some of the associated text from the task

-50-

independent corpus for non-terminal tokens that can be mistaken for one of the desired task dependent semantic or syntactic concepts.

28. A computer readable medium including instructions readable by a computer which, when implemented execute a method to build language model for a language processing system, the method comprising:

- accessing a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application;
- generating word phrases from the plurality of context-free grammars;
- formulating an information retrieval query from at least one of the word phrases;
- querying a task independent corpus based on the query formulated;
- identifying associated text in the task independent corpus based on the query; and
- building a language model using the identified text.

29. The computer readable medium of claim 28 wherein building a language model comprises building a N-gram language model.

30. The computer readable medium of claim 29 and having instructions further comprising:

-51-

parsing the identified text of the task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts;

replacing each of the identified word occurrences with corresponding non-terminal tokens; and wherein building the N-gram language model comprises building a N-gram model having the non-terminal tokens.

31. The computer readable medium of claim 29 and having instructions further comprising:

building a second N-gram language model from the word phrases from the plurality of context-free grammars; and

combining the first-mentioned N-gram language model and the second N-gram language model to form a third N-gram language model.

32. The computer readable medium of claim 31 and having instructions further comprising:

parsing the identified text of the task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts;

replacing each of the identified word occurrences with corresponding non-terminal tokens; and

-52-

wherein the word phrases include non-terminal tokens and wherein building the first-mentioned N-gram language model comprises building a N-gram model having the non-terminal tokens.

33. The computer readable medium of claim 30 and having instructions further comprising:

storing the N-gram model having the non-terminal tokens and the plurality of context-free grammars having non-terminal tokens representing task dependent semantic or syntactic concepts on a computer readable medium.

34. The computer readable medium of claim 28 and having instructions further comprising:

storing the identified text of the task independent corpus separate from the task independent corpus.

35. A computer readable medium including instructions readable by a computer which, when implemented execute a method to build language model for a language processing system, the method comprising:

accessing a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application;

-53-

generating word phrases from the plurality of
context-free grammars;
building a first N-gram language model from the
word phrases;
formulating an information retrieval query from at
least one of the word phrases;
querying a task independent corpus based on the
query formulated;
identifying associated text in the task
independent corpus based on the query;
building a second N-gram language model from the
identified text; and
combining the first N-gram language model and the
second N-gram language model to form a third
N-gram language model.

36. The computer readable medium of claim 35 wherein
building the second N-gram language model
includes using only the identified text.

37. The computer readable medium of claim 36 and
having instructions further comprising:
storing the identified text of the task
independent corpus separate from the task
independent corpus.

38. The computer readable medium of claim 37 and
having instructions further comprising:

-54-

parsing the identified text of the task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts;

replacing each of the identified word occurrences with corresponding non-terminal tokens; and wherein the word phrases include non-terminal tokens and wherein building the first-mentioned N-gram language model comprises building a N-gram model having the non-terminal tokens.

39. The computer readable medium of claim 35 and having instructions further comprising:

parsing the task independent corpus with the plurality of context-free grammars to identify word occurrences for each of the semantic or syntactic concepts;

replacing each of the identified word occurrences with corresponding non-terminal tokens; and wherein the word phrases include non-terminal tokens and wherein building the first-mentioned N-gram language model comprises building a N-gram model having the non-terminal tokens.

40. A computer readable medium including instructions readable by a computer which, when implemented execute

-55-

a method to build a unified language model for a selected application, the method comprising:

accessing a plurality of context-free grammars comprising non-terminal tokens representing semantic or syntactic concepts of the selected application;

building a word language model from a corpus; and assigning probabilities to words of at least some of the context-free grammars as a function of corresponding probabilities obtained for the same terminals from the word language model wherein assigning probabilities includes normalizing the probabilities of the words from the word language model in each of the context-free grammars as a function of the words allowed by the corresponding context-free grammar.

41. The computer readable medium of claim 40 wherein the word language model comprises an N-gram language model.

42. The computer readable medium of claim 40 wherein the corpus comprises a task independent corpus.

43. The computer readable medium of claim 42 and having instructions further comprising:

generating word phrases from the plurality of context-free grammars;

-56-

formulating an information retrieval query from at least one of the word phrases;
querying the task independent corpus based on the query formulated;
identifying associated text in the task independent corpus based on the query; and
wherein building a N-gram language model includes using the identified text.




FIG. 1




FIG. 4




FIG. 2




FIG. 3




FIG. 5




FIG. 6




FIG. 7





FIG. 8



(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 December 2001 (06.12.2001)

PCT

(10) International Publication Number
WO 01/093246 A3

(51) International Patent Classification⁷: **G10L 15/18**

(21) International Application Number: PCT/US01/16851

(22) International Filing Date: 23 May 2001 (23.05.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/585,298 1 June 2000 (01.06.2000) US

(71) Applicant: MICROSOFT CORPORATION [US/US];
One Microsoft Way, Redmond, WA 98052-6399 (US).

(72) Inventors: HUANG, Xuedong, D.; 20020 N.E. 121st
Street, Woodinville, WA 98072 (US). MAHAJAN,
Milind, V.; 17430 N.E. 97th Way, Redmond, WA 98052
(US). WANG, Ye-Yi; 6120 142nd Ct. NE, Redmond, WA
98052 (US). MOU, Xiaolong; 60 Wadsworth Street, Apt.
4D, Cambridge, MA 02142 (US).

(74) Agents: KOEHLER, Steven, M. et al.; Westman, Cham-
plin & Kelly, P.A., International Centre, Suite 1600, 900
Second Avenue South, Minneapolis, MN 55402-3319
(US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ,
NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM,
TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

[Continued on next page]

(54) Title: CREATING A UNIFIED TASK DEPENDENT LANGUAGE MODELS WITH INFORMATION RETRIEVAL TECHNIQUES



(57) Abstract: A method (20) for creating a language model from a task-independent corpus is provided. In one embodiment, a task dependent unified language model (140) is created. The unified language model (140) includes a plurality of context-free grammars (144) having non-terminals and a hybrid N-gram model (142) having at least some of the same non-terminals embedded therein.

WO 01/093246 A3



(88) Date of publication of the international search report:
12 September 2002

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/16851

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G10L15/18

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, INSPEC, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P,X	<p>YE-YI WANG ET AL: "A unified context-free grammar and n-gram model for spoken language processing" 2000 IEEE INTERNATIONAL CONFERENCE ON ACOUSTICS, SPEECH, AND SIGNAL PROCESSING. PROCEEDINGS (CAT. NO.00CH37100), ISTANBUL, TURKEY, 5 - 9 June 2000, pages 1639-1642 vol.3, XP002181416 2000, Piscataway, NJ, USA, IEEE, USA ISBN: 0-7803-6293-4 the whole document</p> <p style="text-align: center;">--- -/--</p>	<p>1-6, 19-21, 23-27, 40-42</p>

☒ Further documents are listed in the continuation of box C.

☐ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

8 November 2001

Date of mailing of the international search report

18. 06. 2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Quélavoine, R

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 01/16851

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	J. GILLET AND W. WARD: "A language model combining trigrams and stochastic context-free grammars" ICSLP'98, 30 November 1998 (1998-11-30) - 4 December 1998 (1998-12-04), XP002181417 Sydney, Australia the whole document	1-3,5, 19-21, 23,24, 26,40-42
Y	--- DATABASE INSPEC [Online] INSTITUTE OF ELECTRICAL ENGINEERS, STEVENAGE, GB; KITA K ET AL: "Improvement of a probabilistic CFG using a cluster-based language modeling technique" Database accession no. 5609794 XP002182302 abstract & METHODOLOGIES FOR THE CONCEPTION, DESIGN, AND APPLICATION OF INTELLIGENT SYSTEMS. PROCEEDINGS OF THE 4TH INTERNATIONAL CONFERENCE ON SOFT COMPUTING, PROCEEDINGS OF THE 4TH INTERNATIONAL CONFERENCE ON SOFT COMPUTING (IIZUKA '96) METHODOLOGIES FOR THE, pages 929-932 vol.2, 1996, Singapore, World Scientific, Singapore ISBN: 981-02-2845-7	1-3,5, 19-21, 23,24, 26,40-42
A	--- METEER M ET AL: "STATISTICAL LANGUAGE MODELING COMBINING N-GRAM AND CONTEXT-FREE GRAMMERS" SPEECH PROCESSING. MINNEAPOLIS, APR. 27 - 30, 1993, PROCEEDINGS OF THE INTERNATIONAL CONFERENCE ON ACOUSTICS, SPEECH, AND SIGNAL PROCESSING (ICASSP), NEW YORK, IEEE, US, vol. 2, 27 April 1993 (1993-04-27), pages 11-37-40, XP000427719 ISBN: 0-7803-0946-4 abstract -----	1-6, 19-21, 23-27, 40-42

INTERNATIONAL SEARCH REPORT

International application No.
PCT/US 01/16851

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☒ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:
1-6, 19-21, 23-27, 40-42

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1-6,19-21,23-27,40-42

creating a unified context-free grammar and N-Gram task dependent language model

2. Claims: 7-18,22,28-39,43

clustering of a task independent corpus into task dependent subparts using information retrieval techniques